

REPORT DOCUMENTATION PAGE			Form Approved OMB NO. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comment regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE 1 September 1997		3. REPORT TYPE AND DATES COVERED Final, 15 August 95 - 14 August 97
4. TITLE AND SUBTITLE Final Technical Report: Optimal Design of Diffractive Optical Structures			5. FUNDING NUMBERS G-F49620-95-1-0497	
6. AUTHOR(S) David C. Dobson				
7. PERFORMING ORGANIZATION NAMES(S) AND ADDRESS(ES) Texas A&M Research Foundation Texas A&M University Department of Mathematics College Station, TX 77843-3368			8. PERFORMING ORGANIZATION REPORT NUMBER	
9. SPONSORING / MONITORING AGENCY NAME(S) AND ADDRESS(ES) U.S. Army Research Office P.O. Box 12211 Research Triangle Park, NC 27709-2211			10. SPONSORING / MONITORING AGENCY REPORT NUMBER	
11. SUPPLEMENTARY NOTES The views, opinions and/or findings contained in this report are those of the author(s) and should not be construed as an official Department of the Army position, policy or decision, unless so designated by other documentation.				
12a. DISTRIBUTION / AVAILABILITY STATEMENT Approved for public release; distribution unlimited.			12 b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words)  An optimal design method for low-order periodic dielectric diffractive structures in E-parallel polarization has been developed. A key property of the method is that nonsmooth design profiles present no theoretical or practical difficulties so that manufacturable designs can be achieved. The method is based on an accurate partial differential equation diffraction model. It has been theoretically justified, implemented, and applied to reveal some unexpected high-efficiency diffractive structures for potential use in photonic and micro-optical devices.  Research associated with the development of the method has led to efficient numerical methods for calculating diffraction through grating structures and improved understanding of total variation methods for image processing and inverse problems, and has established the groundwork for three-dimensional design methods.				
14. SUBJECT TERMS			DTIC QUALITY INSPECTED 4	
			15. NUMBER OF PAGES 4	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OR REPORT UNCLASSIFIED		18. SECURITY CLASSIFICATION OF THIS PAGE UNCLASSIFIED		19. SECURITY CLASSIFICATION OF ABSTRACT UNCLASSIFIED
			20. LIMITATION OF ABSTRACT UL	

Final Technical Report  
Air Force Office of Scientific Research Grant F49620-95-1-0497

## **Optimal Design of Diffractive Optical Structures**

Principal Investigator: David C. Dobson  
Department of Mathematics  
Texas A&M University  
College Station, TX 77843-3368

19971203 269

## Objectives

The objectives of this project were as follows:

- Investigate and develop new optimal design methods based on full PDE diffraction models, to produce effective, manufacturable diffractive structures.
- Work toward substantial improvements in the computational efficiency of optimal design algorithms, so that highly complex problems and 3D geometries become feasible.
- Carry out mathematical analysis to establish fundamental properties of problems and solutions, and to suggest improved computational techniques.

## Status of Effort

A new optimal design method for low-order nonsmooth diffraction grating structures in E-parallel polarization was developed [4, 6]. A key property of the method is that nonsmooth design profiles present no theoretical or practical difficulties so that manufacturable designs can be achieved. The method is based on an accurate partial differential equation diffraction model. The optimal design method finds an interface between two dielectric materials in such a way that the difference between a specified energy and the propagated energy in each diffracted mode is minimized. Total variation constraints are imposed on the interface to ensure that the final design is simple enough to be manufacturable. Through preconditioning of the diffraction problem and the use of an efficient minimization algorithm, the method is fast enough to run interactively on a workstation. It has been theoretically justified, implemented, and applied to reveal some unexpected high-efficiency diffractive structures for potential use in photonic and micro-optical devices. The groundwork for the extension of this method to H-parallel polarization and 3D geometries has been established [1].

Progress in efficient preconditioned finite element methods for diffraction problems made in the course of this project allowed a large computational study to understand the behavior of a proposed micro-electro-mechanical structure (MEMS) for tunable infrared filtering [2, 3]. The problem involved high-contrast conductive media, conical diffraction, resonances, and thousands of runs. The flexibility and robustness of the finite element methods enabled a successful simulation which matched well with experimental data.

Research associated with the development of optimal design techniques has led to improved understanding of total variation methods for image processing [8] and inverse problems [5]. A related investigation of eddy current methods for quantifying flaws in homogeneous metal plates was undertaken [7]. This study yielded a new, relatively stable method for recovering vertically averaged flaw profiles. Potential applications exist for aircraft inspection.

## Transitions

The new optimal design technique for diffractive structures and related research has been applied in an industrial setting with researchers at Honeywell Technology Center. Honeywell has used this technology on several Air Force and Department of Defense related projects, including design of sensors for aircraft and development of MEMS-based devices for optical applications.

## References

- [1] G. Bao and David C. Dobson, *Modeling and optimal design of diffractive optical structures*, Surveys on Math. for Industry, submitted.
- [2] J.A. Cox, D.C. Dobson, T. Ohnstein, and J.D. Zook, *LIGA tunable spectral filter performance*, in Proc. SPIE vol. 3008 (1997).
- [3] J.A. Cox, J.D. Zook, T. Ohnstein, and D.C. Dobson, *Optical performance of high-aspect LIGA gratings*, Opt. Eng. **36** (1997), 1367–1373.
- [4] David C. Dobson and J. Allen Cox, *Optimal design of low order diffractive structures*, in “Diffractive Optics and Micro-Optics”, Vol. 5, OSA Technical Digest Series (Optical Society of America, Washington, DC (1996), 5-8.
- [5] David C. Dobson, *Recovery of blocky images in electrical impedance tomography*, in “Inverse Problems in Medical Imaging and Nondestructive Testing”, H. W. Engl, A. K. Louis, and W. Rundell, eds., Springer-Verlag, Wien (1997), pp. 43–64.
- [6] David C. Dobson, *Optimal shape design of blazed diffraction gratings*, Appl. Math. and Opt., to appear.
- [7] David C. Dobson and Fadil Santosa, *Nondestructive evaluation of plates using eddy current methods*, Int. J. Eng. Sci., to appear.
- [8] David C. Dobson and Otmar Scherzer, *Analysis of regularized bounded variation penalty methods for denoising*, Inverse Problems **12** (1996), 601–617.